

Ti series

- 40mm of Peak to Peak Excursion
- 2.5" Ultra High Temp Copper Wound Voice Coil
- Radial Backplate Venting System
- Easy Connect Single Location Speaker Terminal
- Long Throw Spider Suspension
- Woven Tinsel Leads

- High Excursion CAE/CAD Motor Design
- Vented Titanium-Aluminum Hybrid Former
- One Piece Injected Polypropylene Dustcap
- High Roll Butyl Rubber Double Stitched Surround
- Optimized for Sealed or Vented Enclosures
- Rigid Powder Coated Anti-Resonant Castbasket



	<i>Ti312d4</i>	<i>Ti312d2</i>	<i>Ti310d4</i>	<i>Ti310d2</i>
Size	12"	12"	10"	10"
Power Handling	600w RMS	600w RMS	600w RMS	600w RMS
Impedance	Dual 4 Ohms	Dual 2 Ohms	Dual 4 Ohms	Dual 2 Ohms
Frequency Response	20Hz to 300Hz	20Hz to 300Hz	20Hz to 300Hz	20Hz to 300Hz
Mounting Depth	6.88" - 175mm	6.88" - 175mm	6.22" - 158mm	6.22" - 158mm
Cut Out Diameter	10.86" - 276mm	10.86" - 276mm	9.25" - 235mm	9.25" - 235mm
Overall Diameter	12.63" - 321mm	12.63" - 321mm	10.66" - 271mm	10.66" - 271mm
Peak to Peak Excursion	40mm	40mm	40mm	40mm